

# CardOS V5.0

## Multifunctionality

The smart card operating system for the highest demands



Fullfillment of highest security demands - CardOS V5.0 is a multi-purpose smart card operating system which complies with international smart card standards and provides simple and efficient use in standardized environments and applications.

# Certified security for the highest demands

## Overview

Flexibility, speed and security need to go hand in hand in today's business environment. It's no longer an option to have fixed, static and slow-moving security that prevent business from flowing at the required pace. Yet, security is more critical than ever before.

Smart cards are fast becoming the basis of many of today's security solutions. Atos smart cards are now being used by public authorities, businesses and institutions because they address today's unique business problems.

Through our leading CardOS® solutions, we provide you with smart cards that guarantee identity and control access and make you more efficient for business, customers and people.

Our Atos CardOS V5.0 smart card operating system provides an outstanding level of security and quality. Used in different smart card markets CardOS V5.0 offers a multitude of applications like eID, citizen cards, health insurance and health professional cards, employee badges, signature cards, as well as loyalty cards.

With the CardOS V5.0 Atos has developed a versatile and powerful smart card operating system. It perfectly combines flexibility with the very highest security requirements.

As well, CardOS represents the many years of know-how Atos has developed by being both a world-leading systems integrator and a leader in smart card development.

## Highlights

CardOS V5.0 is a multifunctional native smart card operating system, which is extendable by customized packages to amend or adjust the operating system functionality.

In addition the authentication framework is a flexible option to realize authentication protocols by using configuration data.

With the ICAO functionality (ICAO Doc 9303) CardOS V5.0 is suited for contact based eID projects based on BAC and EAC protocols.

CardOS V5.0 offers state-of-the-art crypto algorithms with AES, SHA-2 and elliptic curves.

The ISO compliant security architecture of CardOS V5.0 supports access rules in expanded format.

Atos CardOS API middleware is available separately and provides the best integration to standard applications on Windows, Linux and Mac OS X.

## Hardware Platform

CardOS V5.0 is based on the innovative digital security technology 'Integrity Guard' from Infineon and is implemented on the SLE78 next generation security controller platform using SOLID FLASH™<sup>1</sup>. SOLID FLASH™ products offer significant value add like increased logistic flexibility and faster time to market.

CardOS V5.0 is available on the chip SLE78CFX3000P providing 96 kByte user memory. Certification covers also the derivatives SLE78CFX2400P and SLE78CFX4000P, which are available on request depending on the memory needs of the application.

CardOS V5.0 is available in wafer form, as M4.8 module, as smart card in ID-1, ID-000 or Micro SIM format and as SMD chip VQFN32.

## Certified security

CardOS V5.0 is certified according to Common Criteria EAL4+ in compliance with:

- ▶ SSCD-PP Type 3 (CWA 14169)
- ▶ German signature law / ordinance on electronic signatures (SigG / SigV)

with respective signature applications.

<sup>1</sup>SOLID FLASH™ is a registered trademark of Infineon Technologies AG.

## Technical Highlights

### Cryptographic Functions and Algorithms

- ▶ 3DES
- ▶ AES up to 256 bit
- ▶ RSA up to 4096 bit
- ▶ ECDH up to 512 bit
- ▶ SHA-1, SHA-224, SHA-256, SHA-384, SHA-512
- ▶ ECDSA up to 512 bit

### Standards

- ▶ ISO 7816 (parts 3, 4, 8 and 9)
- ▶ ICAO Doc 9303 (BAC, EAC)
- ▶ BSI TR-03110 (EACv1, RI)

### Electrical Specification

- ▶ Supply Voltage: 1.62 V to 5.5 V
- ▶ Frequency Range: 1 MHz to 10 MHz
- ▶ Operating Temperature Range: -25 to +85°C (chip, module)

### Chip

- ▶ Infineon SLE78CFX3000P

### Delivery Types

- ▶ Wafer
- ▶ Contact Module M4.8
- ▶ Card format ID-1
- ▶ Card format ID-000
- ▶ Micro SIM
- ▶ SMD Chip VQFN32

## Basic Features

CardOS V5.0 offers the following general features:

- ▶ ISO/IEC 7816 compatible commands
- ▶ Compatibility with the most important international standards providing long-term security for integration in standardized environments (readers, applications, etc.)
- ▶ Expandability of the operating system with the subsequent addition of software packages
- ▶ Integrity protection of all active software packages preventing the use of corrupt software
- ▶ "Command chaining" in accordance with ISO/IEC 7816-4
- ▶ A dynamic, flexible file system based on ISO/IEC 7816-4 with the following characteristics:
  - Number of files and folders with any depth of nesting
  - Support of Short File IDs
  - Dynamic memory management for optimal utilization of the available EEPROM
  - Protection mechanisms against EEPROM defects, power failure and card tearing
  - Flexible Memory Management for RAM and EEPROM
- ▶ Support of CV (card verifiable) certificates
  - Extraction and use of the public key directly from the certificate
  - Verification of certificates and certificate chains.

## eID Support

CardOS V5.0 provides support for contact based eID features according to ICAO DOC9303 and BSI TR-03110

- ▶ Basic Access Control (BAC)
- ▶ Extended Access Control (EACv1)
  - Chip Authentication (CA) with ECDH
  - Terminal Authentication (TA) with ECDSA
- ▶ Restricted Identification (RI) with ECDH.

## CardOS V5.0 – powerful smart card operating system – deployable for diverse applications in different smart card markets.

### Data Security

CardOS V5.0 provides optimal data security with a clearly structured ISO compliant security architecture and a wide variety of extremely flexible protection mechanisms, such as:

- ▶ Different life cycle phases influencing the permitted commands
- ▶ Access Rules in expanded format, stored either in one or more EF.ARRs or supplied directly with the command creating the file or object
- ▶ Secure storage of PINs and keys as objects (without reservation of file IDs)
- ▶ Test objects like PINs defined to allow unlimited or limited (up to 254) uses until a new authentication is necessary („Security Status Evaluation Counter“)
- ▶ Stepwise refinement of the security structure after file generation without loss of data
- ▶ Secure messaging for cryptographically secured communication between the card and the terminal or host.

### Cryptographic Functions

CardOS V5.0 provides a large number of cryptographic functions and algorithms, such as:

- ▶ Symmetric Algorithms
  - Triple DES (CBC) with ISO padding
  - DES MAC3 and Retail MAC with ISO or ANSI padding
  - AES (CBC) with key length 128, 192, 256 bit
  - AES CMAC with ISO padding
- ▶ Asymmetric algorithms
  - RSA based on CRT with an arbitrary public exponent with key length up to 4096 bit
  - PKCS#1-BT1 or PKCS#1-BT2 padding
  - PSS Padding according to PKCS#1 V2.1
  - Elliptic Curve Cryptography based on GF(p) with key length up to 512 bit
- ▶ Calculation of cryptographic hash values with SHA-1, SHA-224, SHA-256, SHA-384, SHA-512
- ▶ Creation and verification of digital signatures with RSA and ECDSA
- ▶ Internal and external key generation for RSA and EC keys
- ▶ Secured key import with Secure Messaging
- ▶ Key Agreement with EC-Diffie-Hellmann (ECDH), EC Key Agreement of ElGamal Type (EC-KAEG)
- ▶ Flexible derivation of session keys
- ▶ True random number generator.



---

# Outstanding convenience by fully complying to global standards

---

## Initialization and Personalization

The partly patented personalization and initialization procedures facilitate cost-efficient mass production of the CardOS V5.0 cards as well as high performance, highly secure modification of existing applications and the addition of new applications in the field.

- ▶ Support of independent personalization for individual applications
- ▶ Integrated security concept for initialization and personalization.

## Communication Protocols

Transmission protocol according to ISO/IEC 7816-3

- ▶ T=1 protocol
- ▶ Support of extended length APDUs according to ISO/IEC 7816-4
- ▶ Up to four logical channels
- ▶ Support of protocol parameter selection (PPS)
- ▶ Support of WTX (Waiting Time eXtension)
- ▶ Fast, selectable card communication with up to 436 kbaud.

## Tools and Support

To help with the integration of CardOS V5.0 the following are offered to customers:

- ▶ Manuals and script files
- ▶ Script tool for executing card commands and loading packages
- ▶ Professional Services:
  - Professional support for integration projects
  - Customized Packages and File Structures
- ▶ CardOS API, the standard cryptographic interface for CardOS token with Microsoft Base CSP and PKCS#11 support
- ▶ Delivery of complete turn-key solutions for registration, usage and revocation of smart cards.

---

## About Atos

Atos is an international information technology services company with annual 2010 pro forma revenues of EUR 8.6 billion and 74,000 employees in 42 countries at the end of September 2011. Serving a global client base, it delivers hi-tech transactional services, consulting and technology services, systems integration and managed services. With its deep technology expertise and industry knowledge, it works with clients across the following market sectors: Manufacturing, Retail, Services; Public, Health & Transport; Financial Services; Telecoms, Media & Technology; Energy & Utilities.

Atos is focused on business technology that powers progress and helps organizations to create their firm of the future. It is the Worldwide Information Technology Partner for the Olympic Games and is quoted on the Paris Eurolist Market. Atos operates under the brands Atos, Atos Consulting & Technology Services, Atos Worldline and Atos Worldgrid.

## Legal remarks

On account of certain regional limitations of sales rights and service availability, we cannot guarantee that all products included in this document are available through the Atos sales organization worldwide. Availability and packaging may vary by country and is subject to change without prior notice. Some / All of the features and products described herein may not be available in the United States or Japan.

The information in this document contains general technical descriptions of specifications and options as well as standard and optional features which do not always have to be present in individual cases. Atos reserves the right to modify the design, packaging, specifications and options described herein without prior notice. Please contact your local Atos sales representative for the most current information.

Note: Any technical data contained in this document may vary within defined tolerances. Original images always lose a certain amount of detail when reproduced.

For more information, contact: [security@atos.net](mailto:security@atos.net)

[atos.net / security](http://atos.net/security)

Atos, the Atos logo, Atos Consulting, Atos Worldline, Atos Sphere, Atos Cloud, Atos Healthcare (in the UK) and Atos Worldgrid are registered trademarks of Atos SA. All trademarks are the property of their respective owners. July 2012 © 2012 Atos.